



quality.always

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

MJ-116. MITASU RACING MOTOR OIL SN 10W-60 100% Synthetic



1L



4L



20L

MITASU RACING MOTOR OIL SN 10W-60 100% Synthetic is manufactured from Esters and PAO Group IV base stock, combined with unique system of enhancing additives of the latest API (American Petroleum Institute) service standard - SN. Designed to work in critical operating conditions.

APPLICATION

MITASU RACING MOTOR OIL SN 10W-60 100% Synthetic is specifically designed for use in highly accelerated sports and racing cars with naturally aspirated and supercharged engines, including those working on the enriched fuel mixtures, equipped with anti-lag systems (ALS) or other design features that increase the level of thermal stress.

TECHNOLOGY MEETS REQUIREMENTS

- API SN



APPLICATION BENEFITS

With high viscosity index and low oil consumption, all-seasons fully synthetic Ester motor oil MITASU RACING MOTOR OIL SN 10W-60 100% Synthetic provides:

- Stable performance over a wide range of temperatures due to the use of Esters and PAO-based oils
- Outstanding engine protection under extreme operating conditions, including racing and competition
- Maintenance of optimal oil pressure regardless of engines operating temperature
- Exceptional oil film strength
- Excellent anti-oxidation properties
- Superior mechanical stability and resistance to the degradation effects of heat

The latest technologies of MITASU OIL CORPORATION, Japan enable MITASU RACING MOTOR OIL SN 10W-60 100% Synthetic to meet and exceed the requirements of the following Original Equipment Manufacturers (OEM): TOYOTA, LEXUS, NISSAN, MAZDA, MITSUBISHI, HONDA, SUZUKI, SUBARU, DAIHATSU, FORD, AUDI, BMW, MB and many others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	10W-60
Density at 15°C	ASTM D-4052	0,8573
Flash point, °C	ASTM D-92	236
TBN (mg KOH/g)	ASTM D-2896	10,00
Pour point, °C	ASTM D-97	-39
Colour	ASTM D-1500	<2,5
Viscosity index	ASTM D-2270	173
Kinematic viscosity at 40°C (cSt)	ASTM D-445	169,80
Kinematic viscosity at 100°C (cSt)	ASTM D-445	23,69

Due to continual product research and development, the information contained herein is subject to change without notification.