



quality.always

# MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan  
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188  
E-mail: info@mitasuoil.co.jp

## MJ-944. MITASU 4-STROKE MA2 20W-40



0,8L, 1L

MITASU 4-STROKE MA2 20W-40 is a premium quality four-stroke engine oil formulated with a high quality base and a modern additive package. Highly resistant to oxidation, the product guarantees optimum wear protection and prevents deposits in the engine.

### APPLICATION

MITASU 4-STROKE MA2 20W-40 is designed for use in the lubricating systems of air-cooled and water-cooled 4T scooter and motorcycle engines, including those, operation continuously under high load conditions. It meets the requirements of JASO MA2 ensures precision operation of the wet-clutch in 4T motorcycles with an integrated transmission, is compatible with aftertreatment systems.

### SPECIFICATIONS / APPROVALS

- API SL/SJ
- JASO MA2

### APPLICATION BENEFITS

MITASU 4-STROKE MA2 20W-40 provides:

- Superior wear protection
- Protection from deposits in the engine
- Stable performance at the wide range of temperatures

The latest technologies of MITASU OIL CORPORATION, Japan enable the four-stroke motorcycle engine oils, manufactured by the company, to exceed the requirements of such motorcycle manufacturers as KAWASAKI, HONDA, YAMAHA and others.

### TECHNICAL CHARACTERISTICS

Technical Property	Method	Result
SAE viscosity classification	SAE J300	20W-40
Density at 15°C	ASTM D-4052	0,8644
Flash point, °C	ASTM D-92	240
TBN (mg KOH/g)	ASTM D-2896	5,53
Pour point, °C	ASTM D-97	-21
Colour	ASTM D-1500	<2,0
Viscosity index	ASTM D-2270	131
Kinematic viscosity at 40°C (cSt)	ASTM D-445	111,60
Kinematic viscosity at 100°C (cSt)	ASTM D-445	14,35

Due to continual product research and development, the information contained herein is subject to change without notification

© 2020 Mitsuru Oil Corporation, Japan.

