

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan Tel: +81-3-5532-8187. Fax: +81-3-5532-8188 E-mail: info@mitasuoil.co.jp

quality.always

MJ-410. MITASU GEAR OIL GL-5 75W-90 100% Synthetic

MITASU GEAR OIL GL-5 75W-90 100% Synthetic is a premium quality fully synthetic transmission oil, fortified with sulfur-phosphorous anti-wear and anti-scoring additives. This product is designed for high performance under extreme loads (EP type - Extreme Pressure).

APPLICATION

MITASU GEAR OIL GL-5 75W-90 100% Synthetic is suitable for application in differentials, axles, speed transfer cases and steering equipment of vehicles under maximum load conditions where the use of a transmission oil of API GL-5, SAE 75W-90 standard is recommended by the equipment manufacturer.

SPECIFICATIONS / APPROVALS

- · API GL-5
- · API MT-1
- · MIL-PRF-2105E
- · EP type (extreme pressure)

APPLICATION BENEFITS

MITASU GEAR OIL GL-5 75W-90 100% Synthetic provides:

- · Extended friction protection of transmission parts operating under heavy load conditions
- · Stable performance at temperatures as low as 45 °C
- · Extended drain interval
- · Extended transmission service life
- · Protection against rust

The latest technologies of MITASU OIL CORPORATION, Japan enable transmissions oils manufactured by the company to exceed the requirements of such car manufacturers as TOYOTA, LEXUS, NISSAN, MAZDA, MITSUBISHI, HONDA, SUZUKI, SUBARU, DAIHATSU, HYUNDAI, KIA, FORD, MERCEDES-BENZ, VW, FIAT, AUDI, VOLVO, PORSCHE and others.

TECHNICAL CHARACTERISTICS

Technical property	Method	Result
SAE viscosity grade	SAE J300	75W-90
Density at 15°C	ASTM D-4052	0,8708
Flash point, °C	ASTM D-92	220
Pour point, °C	ASTM D-97	- 45
Colour	ASTM D-1500	< 1,5
Viscosity index	ASTM D-2270	208
Kinematic viscosity at 40°C (cSt)	ASTM D-445	68,39
Kinematic viscosity at 100°C (cSt)	ASTM D-445	13,68

Due to continual product research and development, the information contained herein is subject to change without notification.

© 2012 Mitasu Oil Corporation, Japan.



4L



20L



200L

