



quality.always

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku, Tokyo, 105-0003, Japan
Tel: +81-3-5532-8187. Fax: +81-3-5532-8188
E-mail: info@mitasuoil.co.jp

MJ-412. MITASU GEAR OIL GL-5 85W-90 LSD



1L

MITASU GEAR OIL GL-5 85W-90 LSD is premium quality transmission oil intensified by a new generation group of high technological additives to meet the TOYOTA OEM (Original Equipment Manufacturer) requirements.

APPLICATION

MITASU GEAR OIL GL-5 85W-90 LSD is suitable for application in limited slip differentials (LSD) of TOYOTA vehicles (Friction-type or Mechanical-type), operating under heavy load conditions, where GL-5 oil is recommended. It ensures low noise levels and protection against wear. Can be used in various transmissions of vehicles made by other manufacturers, where the proper oil specifications and viscosity are recommended.

SPECIFICATIONS / APPROVALS

- API GL-5
- LS type (Limited Slip)

APPLICATION BENEFITS

MITASU GEAR OIL GL-5 85W-90 LSD provides:

- Compliance with the highest requirements of TOYOTA OEM (Original Equipment Manufacturer)
- Long-term friction protection
- Stable performance of characteristics in a wide range of temperatures
- Excellent protection against wear



4L



20L

MITASU GEAR OIL GL-5 85W-90 LSD is designed for TOYOTA and also meets the requirements of most Japanese, American and European car manufacturers such as LEXUS, NISSAN, MAZDA, HONDA, MITSUBISHI, SUZUKI, SUBARU, DAIHATSU, HYUNDAI, KIA, FORD, VW, FIAT, AUDI and others.

TECHNICAL CHARACTERISTICS



200L

Technical property	Method	Result
SAE viscosity grade	SAE J300	85W-90
Density at 15°C	ASTM D-4052	0,8933
Flash point, °C	ASTM D-92	212
Pour point, °C	ASTM D-97	-27
Colour	ASTM D-1500	3,0
Viscosity index	ASTM D-2270	105
Kinematic viscosity at 40°C (cSt)	ASTM D-445	186,48
Kinematic viscosity at 100°C (cSt)	ASTM D-445	17,40

Due to continual product research and development, the information contained herein is subject to change without notification.