

MITASU OIL CORPORATION

1-2-9, Nishi Shimbashi, Minato-Ku,Tokyo, 105-0003, Japan Tel: +81-3-5532-8187. Fax: +81-3-5532-8188 E-mail: info@mitasuoil.co.jp

quality.always

MATERIAL SAFETY DATA SHEET

1.	PRODUCT IDENTIFICATION AND COMPANY											
	Issue Date	01.01	01.01.2020									
	Validity Period	3 yea	3 years									
	Product Name	МІТА	SU P	Synthetic								
	Product Code											
		Mitas	su Oil	Cor								
	Producer	Tel: -	1-2-9, Nishi Shimbashi, Minato-Ku,Tokyo, 105-0003, Japan Tel: +81-3-5532-8187. Fax: +81-3-5532-8188 E-mail: info@mitasuoil.co.jp									
2.	COMPOSITION											
	Base Oil Content	70	-	85	%							
	Additives Content	15	-	30	%							
3.	HAZARDS IDENTIFICATION											
	Human Health Product is not hazardous.											
	Eye Contact	Slightly irritant.										
	Inhalation		Repeated and prolonged over-exposure to oil mists may cause irritation or discomfort.									
	Ingestion	Minimal toxicity.										
	Safety Hazards	Not c										
	Environmental Hazards	Not r	Not readily biodegradable.									
4.	FIRST AID											
	Eye Contact		Flush eyes with large amount of water until irritation subsides. If irritation persists, get medical attention.Flush with large amount of water; use soap if available. Remove contaminated clothing. If irritation persists, get medical attention.									
	Skin Contact											
	Inhalation	Rem	tion.									
	Ingestion	Do not induce vomiting. If rapid recovery does not occur, get medical attention.										
5.	FIRE SAFETY											

	Flash Point	>	213	°C									
	Flammable Limit	Not classified as flammable but will burn. Hazardous combustion products may include carbon monoxide, oxides of sulphur, and unidentified organic and inorganic compounds.											
	Autoignition Temp	> 308 °C											
	Specific Hazards	Not classified as flammable but will burn. Hazardous combustion products may include carbon monoxide, oxides of sulphur, and unidentified organic and inorganic compounds.											
	Fire Fighting	Use dry chemical, foam or carbon dioxide to extinguish fire. Water may cause splattering or frothing. Use water to cool and protect fire-exposed material. Wear protective equipment during fire fighting.											
6.	ACCIDENTAL RELEAS	SE MI	E MEASURES										
	Clean-up Procedure	gene remo	Stop the source of leak or release and contain spill if possible. Cover spill with generous amount of inert absorbent material such as sand or earth. Sweep up and remove to suitable, clearly marked containers for disposal in accordance with local regulati.										
7.	HANDLING AND STOP	-											
	Handling	Handling temperatures should not exceed 70°C. Wear proper safety protective equipment. Wash hands thoroughly after handling. Water contamination and spillage should be avoided.											
	Storage	Storage temperatures should be maintained between 0 to 50°C. Odorous and toxic fumes may be evolved from decomposition of product if stored above the safe temperature.											
8.	EXPOSURE CONTROL	L/PERSONAL PROTECTION											
	Exposure Limits		Threshold Limit Values for oil mist is recommended to be controlled at 5 mg/m3 or lower for exposure of 8 hours daily.										
	Ventilation	Exha	Exhaust ventilation to keep below exposure limits.										
	Eye Protection	Wea	r safety	/ glas	sses	or face shields if s	plasł	ning is likely to occur.					
	Skin Protection	Avoi	d repea	ated a	and p	orolonged contact	with p	product. Use oil resistant glove	es.				
	Respiratory Protection	Not normally required unless in confined space.											
	Body Protection	Use proper protective equipment to avoid contact. Wear PVC apron if splashes are likely to occur.											
9.	PHYSICAL AND CHEM	IICAL	PROF	PERT	IES								
	This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not be construed as guaranteeing any specific property of the product.												
	TEST DESCRIPTION		UN	IT		METHOD		TYPICAL RESULTS					
	Appearance		-			Visual		B & C					
	Color		-			D 1500		<2,5					
	Density at 15 °C		kg.	/I		D 4052		0,8512					
	Kinematic Viscosity at 40 °C		cS	St		D 445		70,11					

1.	Kinematic Viscosity at 100 °C	cSt	D 445	11,88							
_	Viscosity Index	-	D 2270	171							
-	Total Base Number	mgKOH/g	D 2896	8,00							
	Flash Point, COC	°C	D 92	218							
	Pour Point	°C	D 97	-42							
	CCS	сР	D 5293	5086							
10.	STABILITY AND REACTIVITY										
	Stability Product is stable under normal use conditions.										
	Thermal Decomposition	Carbon monoxide, carbon dioxide, oxides of sulphur and nitrogen and organic and inorganic compound may evolve when subject to heat or combustion.									
	Hazardous Polymerisation	Will not occur under normal conditions.									
	Incompatible Materials	Strong oxidizing agents. Strong acids									
11.	TOXICOLOGICAL INFORMATION No toxicological data is available for this product. Information is provided based on										
	Basis	oduct. Information is provided t stock used.	based on								
	Acute Exposure Oral										
	Acute Exposure Skin	LD 50 expected to b									
	Inhalation	Repeated or prolonged exposure to oil mists may cause irritation. Slightly irritant. Not a skin irritant unless repeated or prolonged contact. Slight irritant.									
	Eye Irritation										
	Skin Irritation										
	Respiratory Irritation										
	Carcinogenicity	No data to suggest that product is carcinogenic.									
		No data to suggest that product is mutagenic.									
	Mutagenicity	No data to suggest	that product is mutager								
	Mutagenicity Other Information	Brief contact with us		o have serious effect in human	s if the						
		Brief contact with us oil is removed thoro Used engine oils ma use. The concentrat	sed oil is not expected t ughly by washing with ay contain harmful impu- tion of such impurities v	o have serious effect in human	uring sent						
		Brief contact with us oil is removed thoro Used engine oils ma use. The concentrat risks to health and t	sed oil is not expected t ughly by washing with ay contain harmful impu- tion of such impurities v	o have serious effect in human soap and water. urities that have accumulated d will depend on use and they pre	uring sent						
		Brief contact with us oil is removed thoro Used engine oils ma use. The concentrat risks to health and t with caution.	sed oil is not expected t ughly by washing with ay contain harmful impu- tion of such impurities w he environment on disp	o have serious effect in human soap and water. urities that have accumulated d will depend on use and they pre	uring sent andled						

	Mobility	Liquid under most environmental conditions. Floats on water. It is absorbed by soil and will not be mobile.										
	Persistence/ Degradability	Not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.										
	Bioaccumulation	Has the potential to bioaccumulate.										
	Ecotoxicity	Poor soluble mixture. Practically non-toxic to aquatic organisms. May cause physical fouling of aquatic organisms.										
13.	DISPOSAL CONSIDE	DISPOSAL CONSIDERATION										
	Product Disposal		Used or waste oil should be recycled or disposed off in conformity to local disposal regulations. Contact local authorities for approved disposal contractor.									
	Container Disposal	properly di	Empty drums should be completely drained and sent to a drum reconditioner or properly disposed of. Non-reusable small containers should be recycled or disposed of. Ensure conformity to local disposal regulations.									
14.	TRANSPORT INFOR	MATION										
	General Information	Not dangerous for conveyance under UN, IMO, ADR/RID and IATA/ICAO codes.										
15.	REGULATORY INFO	RMATION										
	Not Applicable.											
16.	OTHER INFORMATION											
	The above information is based on data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon the condition that the person receiving it shall make his own determination the suitability of the material for his particular purpose. Therefore, no warranty either express or implied merchantability or fitness for particular purpose is made with respect to the product or the information contained herein.											